

V1.0





1

JY-CS-A01

2



±



25cm 750cm  
15°

3



	7- 30VDC ( 12V)
	RS485
	24V 73mA 1. 7W

---

	0-7.5
	±
	9600, n, 8, 1
	2400, 4800, 9600, 19200, 38400, 115200

RS485	8	1		9600bps
-------	---	---	--	---------

Modbus-RTU	CRC-16/MODBUS	0x01	0x03	0x06
------------	---------------	------	------	------

		0x03			CRC16
(Byte)	1	1	2	2	2

		0x03			CRC16
(Byte)	1	1	1	N	2

		0x06			CRC16
(Byte)	1	1	2	2	2

		0x06			CRC16
(Byte)	1	1	2	2	2

	0x0100		16	500ms	mm
	0x0101		16	100ms	mm

0x0102

.0

# 1

	- 25	25	80		
		65%	90%	RH	1
	- 15	25	60		
		65%	80%	RH	1


(1) a                      0- 39                                      90%


      b                      40- 50

# 2

	7.0	24.0	30.0	V	1
	50		75	mA	
			50	mV	
			100	mV	
ESD			± 200/± 2K	V	2
ESD			± 4K/± 8K	V	3

PVC                                      100cm                                      7.5cm





:

1

2



①

②


③

④

3

①

②



# 1



# 2




JYDAM

<https://www.juyingel.com.cn/software/software/JYDAM%E8%B0%B3%E8%AF%95%E8%BD%AF%E4%BB%B6.rar>

<https://www.juyingel.com.cn/software/jynet/%E4%BB%A5%E5%A4%AA%E7%BD%91%E9%85%8D%E7%BD%AE%E8%BD%AF%E4%BB%B6.rar>

( )



JYDAM






JYDAM

<https://www.juyingelectronics.com.cn/software/software/JYDAM%E8%B0%B3%E8%AF%95%E8%BD%AF%E4%BB%B6.rar>

<https://www.juyingelectronics.com.cn/software/jynet/%E4%BB%A5%E5%A4%AA%E7%BD%91%E9%85%8D%E7%BD%AE%E8%BD%AF%E4%BB%B6.rar>

( )



JYDAM

